



|  |         |      |         |      |      |
|--|---------|------|---------|------|------|
| LIFTING CAPACITY   | 14 T    |      |         |      |      |
| HOOKLIFT WEIGHT  | 2300    |      | 2600    |      |      |
| TOTAL LENGTH (E)   | 4800    | 5000 | 5285    | 5485 | 5685 |
| HOOK-ROLLER CENTRE DISTANCE (C)                                    | 4500    | 4700 | 5000    | 5200 | 5400 |
| CONTAINER WORKING LENGTH (LC min)                                  | 3300    |      | 3800    |      |      |
| CONTAINER WORKING LENGTH(LC max)                                   | 5100    | 5300 | 5600    | 5800 | 6000 |
| HOOK HEIGHT (A)  | 1570    |      |         |      |      |
| CONTAINER PICKING UP HEIGHT (H)                                    | -650    |      | -380    |      |      |
| HOOKARM STROKE (N)   | 575     | 775  | 625     | 825  | 1025 |
| HOOKARM STROKE (N1)  | 825     |      |         |      |      |
| WIDTH OF THE FRAME   | 1060    |      |         |      |      |
| MAX TILTING ANGLE ( $\alpha$ )                                     | 62°     |      | 56°     |      |      |
| LOADING ANGLE (max/min)*   | 24°/49° |      | 23°/44° |      |      |
| OPERATING PRESSURE (bar)   | 310     |      | 330     |      |      |
| PUMP DELIVERY / 1000 r (Lt / min)                                  | 60      |      |         |      |      |
| OIL TANK (Lt)  | 70      |      |         |      |      |
| CENTRE OF GRAVITY<br>(Dimension referred to sliding roller centre) | 2720    | 2750 | 2800    | 2820 | 2850 |

\* truck height: 1100 mm.